Revision: 15.12.2017 Printing date 15.12.2017 Version number 2 SECTION 1: Identification of the substance/mixture and of the company/ undertaking · 1.1 Product identifier • Trade name: Henry Schein Silicone Spray REF: 9002402 · Article number: 540 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Lubricant • 1.3 Details of the supplier of the safety data sheet European Authorised Representative: · Manufacturer/Supplier: Henry Schein Inc. Henry Schein Services GmbH 135 Duryea Road Monzastrasse 2a Melville, NY 11747 63225 Langen USA Germany • Further information obtainable from: Regualtory Affairs Europe cbdeurope@henryschein.com • 1.4 Emergency telephone number: +49 - (0) 6132 - 84463 GBK GmbH (24h - 7d/w - 365d/a) **SECTION 2: Hazards identification** - 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May Aerosol 1 burst if heated. GHS09 environment Aquatic Chronic 2 H411 *Toxic to aquatic life with long lasting effects.* GHS07 H315 Skin Irrit. 2 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

GB

(Contd. on page 2)

GB


Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017





SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous compone	ents:	
CAS: 74-98-6	propane	25-50%
EINECS: 200-827-9	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 106-97-8	butane	10-25%
EINECS: 203-448-7	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
	·	(Contd. on page 3)

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

Trade name: Henry Schein Silicone Spray

G 4 G 0 0 7 5 1 0 4		d. of page 2	
CAS: 9275-10-4	EG-Nr. 927-510-4Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cyclene	10-25%	
	Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 4, H413		
CAS: 9312-54-9 EG-Number 931-254-9 Carbon Hydrates, C6, Isoalkanes, 5% n-hexane		10-25%	
	� Flam. Liq. 2, H225; � Asp. Tox. 1, H304; � Aquatic Chronic 2, H411; � Skin Irrit. 2, H315; STOT SE 3, H336		
CAS: 110-54-3	n-hexane	≤ 2.5%	
	 Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. H315; STOT SE 3, H336 		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

• 5.3 Advice for firefighters

• Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

Trade name: Henry Schein Silicone Spray

(Contd. of page 3)

• 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

• 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** Store in a cool location. Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Not required.

• Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

Trade name: Henry Schein Silicone Spray

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.
- · Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR

Butyl rubber, BR · Eye protection:



Tightly sealed goggles

*

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:
- Form:AerosolColour:Colourless• Odour:Characteristic

(Contd. on page 6)

GB

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

Trade name: Henry Schein Silicone Spray

	(Contd. of page :
Odour threshold:	Not determined.
pH-value:	Not applicable
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. 2: -44 °C
Flash point:	-97 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	1,5 Vol % (Propan/Butan) 10,9 Vol % (Propan/Butan)
Vapour pressure at 20 °C:	5300 hPa
Density: Relative density Vapour density Evaporation rate	Not determined. Not determined. Not determined. Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not applicable. Not determined. Not applicable. Not determined.
Solvent content: VOC (EC)	70 %
Solids content: 9.2 Other information	0 % No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

(Contd. on page 7)

GB

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

(Contd. of page 6)

Trade name: Henry Schein Silicone Spray

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

 \cdot 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

• Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

• Ecotoxical effects:

• Remark: Toxic for fish

• Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Generally not hazardous for water

(Contd. on page 8)

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

(Contd. of page 7)

Trade name: Henry Schein Silicone Spray

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST

16 05 00 gases in pressure containers and discarded chemicals

16 05 04 gases in pressure containers (including halons) containing dangerous substances

• Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
	2 5F Gases. 2.1
Label	
Label	
Class Label IMDG, IATA	
Label	

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

Trade name: Henry Schein Silicone Spray

	(Contd. of page
Label	2.1
14.4 Packing group	
ADR, IMDĞ, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
14.7 Transport in bulk according to An	nex II
of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ):	E0
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008 GHS label elements
- · Directive 2012/18/EU

*

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Printing date 15.12.2017

Version number 2

Revision: 15.12.2017

Trade name: Henry Schein Silicone Spray

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Regualtory Affairs Europe

· Contact: cbdeurope@henryschein.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

• * Data compared to the previous version altered.